




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : A61F 2/44	A2	(11) International Publication Number: WO 93/10725 (43) International Publication Date: 10 June 1993 (10.06.93)
(21) International Application Number: PCT/GB92/02232 (22) International Filing Date: 1 December 1992 (01.12.92) (30) Priority data: 9125798.0 4 December 1991 (04.12.91) GB (71) Applicant (for all designated States except US): CUSTOM-FLEX LIMITED [GB/GB]; Unit 18A, Goldthorpe Industrial Estate, Goldthorpe, Rotherham, South Yorkshire S63 9BL (GB). (72) Inventor; and (75) Inventor/Applicant (for US only) : BULLIVANT, Michael [GB/GB]; 62 Cantley Lane, Bessacarr, Doncaster, South Yorkshire DN4 6NQ (GB). (74) Agents: SHERRARD-SMITH, Hugh et al.; Appleyard Lees, 15 Clare Road, GB-Halifax, West Yorkshire HX1 2HY (GB).		(81) Designated States: AT, AU, BB, BG, BR, CA, CH, CS, DE, DK, ES, FI, GB, HU, JP, KP, KR, LK, LU, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>

(54) Title: IMPROVEMENTS IN OR RELATING TO SPINAL VERTEBRAE IMPLANTS



(57) Abstract

A plate (10) includes a raised platform (20) which rests in a channel in a vertebrae to prevent sideways movement of the plate. A rib (22) extends into a groove formed in the base of the channel to help prevent relative forwards and backwards movement of the plate (10) through the channel. A plate (12) is similarly secured to the facing surface of an adjacent vertebrae. A spacer (12) is inserted between the parts (10) and (14). The spacer (12) includes a downwardly facing convex surface (28) and a flat upwardly facing surface (30). The convex surface (28) slides in a concave recess (32) provided on top of the plate (14) and the flat surface (30) slides against a downwardly facing flat surface (34) of the upper plate (10).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

- 1 -

IMPROVEMENTS IN OR RELATING TO SPINAL VERTEBRAE IMPLANTS.

The present invention relates to a spinal implant, an implant and a spine incorporating an implant. The invention is particularly but not exclusively applicable to implants for spinal vertebrae such as human vertebrae.

A spinal vertebral disc replacement would be performed when one of the discs which lie between the bodies of the vertebrae, has become damaged or dislocated giving rise to what is commonly known as a "slipped disc". These cases tend to be treated by removing the old disc and packing the space with bone chips. The disadvantages of this method are the unreliability of the results and the loss of mobility experienced by the patient in the lower back.

The aim of a spinal disc prosthesis is to replace the damaged disc while maintaining function and stability in the patients back. There are at present very few spinal disc replacement systems available in the world. They comprise generally of a pair of metal plates, one of which is placed on the upper of the two vertebrae and the other on the lower. A polyethylene bearing is then pushed between the plates to provide stability with a degree of motion. The problems of existing systems are that the polyethylene component tends to be contoured (convex) on both sides which enables it to locate in two concave depressions, one each in the centre of the two plates. This requires that both plates be exactly in line with each other or the polyethylene insert cannot be located. In order that alignment can be consistently achieved, it is necessary to have complex instrumentation which makes the operation difficult to perform. The second major problem with existing systems is one of fixation of the

- 2 -

metal plates to the bone of the vertebrae. Although once in place the components are under constant compression, this does not prevent rotation of the plates or sideways movement, both of which are extremely undesirable. To
5 date this problem has been addressed by having small spikes on the back of the metal plates which are embedded in the bone. These however do not provide good fixation and could easily work loose, neither do they allow for any bony integration with the implant.

10

According to one aspect of the present invention a method of securing an implant into an animal bone comprises removing a portion of the bone to form a first pair of spaced opposed generally planar abutment surfaces
15 which face each other and locating the implant such that the implant engages with the abutment surfaces to restrict movement of the implant relative to the bone in a direction towards either abutment surface.

20 The abutment surfaces may be substantially parallel to each other.

The method may comprise removing substantially all of the bone between the abutment surfaces and locating the
25 implant to substantially fill the space between the abutment surfaces.

The method may comprise removing a portion of the bone to form a second pair of spaced opposed abutment
30 surfaces which extend at an angle to the first pair of abutment surfaces and locating the implant such that the implant engages with the second pair of abutment surfaces to restrict movement of the implant in the direction towards either of the second pair of abutment surfaces.

35

- 3 -

A second pair of spaced opposed abutment surfaces may face each other. The second pair of abutment surfaces may be formed by a rotating drill.

5 The second pair of abutment surfaces may be located in a part of the bone which is exposed only after the formation of the first pair of abutment surfaces.

10 The method may comprise forming a first pair or a first and second pair of abutment surfaces as previously referred to in a second bone with a different component of the implant being arranged to engage with the first or the first and second abutment surfaces.

15 The method may comprise securing the implant to a vertebrae such as a human vertebrae.

20 The present invention also includes a combination comprising a bone and an implant in which the implant has been secured by a method as herein referred to.

25 According to another aspect of the present invention an implant comprises a first pair of spaced opposed generally planar abutment surfaces which face away from each other, the abutment surfaces being arranged to abut with correspondingly spaced opposed generally planar abutment surfaces of a bone which face each other.

30 The planar abutment surfaces may be substantially parallel to each other.

35 The implant may include a second pair of spaced abutment surfaces which extend at an angle to the first pair and which are also arranged to abut with correspondingly spaced opposed generally planar abutment

- 4 -

surfaces of a bone. The second pair of surfaces may be comprised by an elongate rib of partially arcuate cross-section.

- 5 The first, or alternatively, the first and second pairs of abutment surfaces may be comprised on a first component.

- 10 The implement may include a third pair of spaced abutment surfaces spaced from the first and second pairs the third pair of abutment surfaces facing away from each other, the third pair of abutment surfaces being arranged to abut with correspondingly spaced opposed generally planar abutment surfaces of a bone which face each other.
- 15 The planar abutment surfaces with which the third pair are arranged to cooperate may be substantially parallel to each other. The implant may include a fourth pair of spaced abutment surfaces which extend at an angle to a
- 20 third pair and which are also arranged to abut with correspondingly spaced opposed generally planar abutment surfaces of a bone. The fourth pair of abutment surfaces may be comprised by an elongate rib of particularly arcuate cross-section. The third or, alternatively, the
- 25 third and fourth pairs of abutment surfaces may be comprised on a second component of the implant.

The implant may be arranged to cooperate with surfaces of a spinal bone.

- 30 According to a further aspect of the present invention a spinal implant comprises a first component arranged, in use, to be secured to a first vertebrae and a second component arranged, in use, to be secured to a second vertebrae, the first and second components being

- 5 -

arranged, in use, to move both transversely and in a curved direction relative to each other.

5 The relative transverse and curved movements may be arranged to occur simultaneously.

10 The components may be arranged to move transversely relative to each other in two different directions. The components may be arranged to move in a curved direction relative to each other in at least two different directions.

15 The implant may include an intermediate component arranged to be located between the first and second component, the intermediate component being arranged, in use, to move in a transverse direction relative to the first component and in a curved direction relative to the second component. The intermediate component may include a generally planar surface arranged to slide against a generally planar surface of the first component. The intermediate component may include a curved surface arranged to slide in a correspondingly inversely shaped curved surface of the second component. The curved surface may be part spherical. The curved surface of the intermediate component may be convex and that of the second component may be concave.

20 According to another aspect of the present invention a spine incorporates a spinal implant located between adjacent vertebrae comprises adjacent vertebrae moving transversely and in a curved direction relative to each other.

25 The spine may comprise the transverse and curved relative movement occurring simultaneously.

- 6 -

According to another aspect of the present invention a method of attaching a spinal implant to two adjacent vertebrae comprises securing a first and second component of the implant to respective adjacent vertebrae and
5 locating an intermediate component between the first and second components.

The method may comprise the intermediate component being selected from one of a plurality of intermediate
10 components of different sizes.

The present invention includes any combination of the herein referred to features or limitations.

15 The present invention may be carried into practice in various ways, but one embodiment will now be described by way of example and with reference to the accompanying drawings in which:-

20 Figures 1a and 1b are a front and a side view respectively of an implant assembly comprising an upper plate 10, a lower part or plate 14 and a spacer 12, the assembly being located between spaced vertebrae 16 and 18;

25 Figures 2a, 2b, 2c, 2d and 2e are an /underneath, front, side, front and plan view respectively of the upper plate 10;

30 Figures 3a, 3b, 3c and 3d are a plan, front, side and front perspective view respectively of the lower plate 14;

Figures 4a, 4b, 4c and 4d are a plan, front, side and front perspective view respectively of the spacer 12.

- 7 -

As shown in Figure 1, the implant assembly comprises the upper and lower plates 10 and 14 and the spacer 12. The way in which the components of the assembly co-operate will be described later, and the fixing of the plates 10 and 14 to their respective vertebrae will now be described.

The vertebrae are first accessed through the abdominal region of the patient and the two vertebrae 16 and 18 are clamped in a common jig (not shown) which restrains the vertebrae against relatively translational or rotational movement.

The jig is provided with aligned guides in order that a rectangular channel can be removed from the facing surfaces of each vertebrae. The bone is removed with conventional techniques such as "shaving" with a chisel. The channels extend from the front to the rear of the vertebrae and the side walls of the channels prevent the plates from sliding in a direction transverse to the extent of the channels. The channel is removed in order to take away the periosteum (the outer bone membrane) and the cortex (the hard outer shell) and to expose the cancellous (the honeycomb of blood and fat).

25

An angled semicircular groove is then cut in the facing surfaces of each rectangular channel. The semicircular grooves are cut by pushing a rotating drill through guide holes in the jig which control precisely the location of the grooves.

30

The vertebrae are now ready for the attachment of the plates.

- 8 -

As shown in Figures 2a to 2e the upper plate 10 is provided with a raised platform 20 having a width and depth corresponding to those dimensions of the channel in the bone to restrict sideways movement of the plate. The plate 10 also includes a semicircular rib 22 extending upwardly from the top of the platform at an angle to the sides of the platform. The rib 22 corresponds in direction and dimension to the groove which has been cut in the vertebrae 16 and helps prevent relative movement *forwards and backwards in the direction of the channel.

Accordingly, when the plate 10 is offered to the vertebrae 16, the sides of the channel guide the plate in the front to back direction and the plate can only be pushed up into full engagement with the vertebrae 16 when the rib 22 is aligned with the semicircular groove in the vertebrae in order that the rib can fill the groove.

The lower plate 14 is attached to the vertebrae 18 in much the same way. Thus a channel and semicircular groove are cut in the upwardly facing surface of the vertebrae, and the plate 14 is provided with a downwardly facing platform 24 and a semicircular rib 26 which co-operate with the channel and groove cut in the bone in order to locate the plate 14 on the bone.

The platforms and ribs of the parts 10 and 14 can be sprayed with titanium to provide a rough, hard finish. Before the plates are fixed to the bone surfaces of the plate which are to co-operate with the bone they may be coated with Hydroxy Apatite, a calcium based material, which helps to prevent rejection by the body of the implant and which assists in the bonding of the parts to the bone.

35

- 9 -

The parts 10 and 14 are now secured to the vertebrae in a precisely spaced and aligned relationship with lateral or rotational movement of each part relating to its supporting bone being prevented by abutment of co-
5 operating parts.

The spacer 12 of polyethylene is then inserted between the parts 10 and 14. As shown in Figures 1a and 1b and Figures 4a to d, the spacer includes a downwardly
10 facing convex surface 28 and a flat upwardly facing surface 30. The convex surface 28 is arranged to slide in a concave recess 32 (see Figure 3d) provided on the top of the part 14. The flat surface 30 is arranged to slide
15 against a downwardly facing flat surface 34 of the upper part 10. The thickness of the spacer 12 can be varied to suit the particular requirement of the patient. The natural tension in the vertebrae ensures that the vertebrae are biased together to trap the spacer in place.

20 The co-operating convex and concave surfaces of the spacer 12 with the plate 14 allows the vertebrae 18 to pivot relative to each other. The co-operating flat surfaces of the spacer 12 and the plate 10 allows the vertebrae to slide transversely in the plane of those co-
25 operating surfaces. This transverse sliding movement is the first such movement that the applicant is aware of which is provided in implants. Traditional medical opinion is that no such movement should be allowed as none would appear to occur in a healthy spinal system.
30 However, the mechanics of spinal operations are extremely complicated and the operation to gain access to the vertebrae can alter the governing parameters as the spine muscles are cut. Accordingly that muscle tissue will scar and the muscles no longer act on the vertebrae in the
35 conventional way. It is believed that the provision of a

- 10 -

small amount of transverse sliding movement between the vertebrae enables considerable transverse forces which can act between vertebrae having conventional implants to be relieved thereby reducing stress on the attachment of the plates to the vertebrae.

Although the upper and lower plates are extremely accurately aligned relative to each other, an additional advantage of providing relative transverse movement is that, as the spacer can slide relative to the plate the components can move to find their own alignment position, should that not be exactly where the previous aligned position was, for example.

It can be seen that the concave and convex surfaces extend through approximately 90° and thus there is virtually no chance of the implant escaping from between the plates under normal pivotal movement of the vertebrae.

- 11 -

CLAIMS

1. A spinal implant comprising a first component arranged, in use, to be secured to a first vertebrae and
5 a second component arranged, in use, to be secured to a second vertebrae, the first and second components being arranged, in use, to move both transversely and in a curved direction relative to each other.
- 10 2. An implant as claimed in Claim 1 in which the relative transverse and curved movements are arranged to occur simultaneously.
- 15 3. An implant as claimed in Claim 1 or 2 in which the components are arranged to move transversely relative to each other in two different directions.
- 20 4. An implant as claimed in any preceding claim in which the components are arranged to move in a curved direction relative to each other in at least two different directions.
- 25 5. An implant as claimed in any preceding claim including an intermediate component arranged to be located between the first and second components, the intermediate component being arranged, in use, to move in a transverse direction relative to the first component and in a curved direction relative to the second component.
- 30 6. An implant as claimed in Claim 5 in which the intermediate component includes a generally planar surface arranged to slide against a generally planar surface of the first component.

- 12 -

7. An implant as claimed in Claim 5 or 6 in which the intermediate component includes a curved surface arranged to slide in a correspondingly inversely shaped curved surface of the second component.

5

8. An implant as claimed in Claim 7 in which the curved surface is part spherical.

9. An implant as claimed in Claim 7 or 8 in which the curved surface of the intermediate component is convex and that of the second component is concave.

10

10. A spine incorporating a spinal implant located between adjacent vertebrae with adjacent vertebrae moving transversely and in a curved direction relative to each other.

15

11. A spine as claimed in Claim 10 comprising the transverse and curved movement occurring simultaneously.

20

12. An implant comprising a first pair of spaced opposed generally planar abutment surfaces which face away from each other, the abutment surfaces being arranged to abut with correspondingly spaced opposed generally planar abutment surfaces of the bone which face each other.

25

13. An implant as claimed in Claim 12 in which the planar abutment surfaces are substantially parallel to each other.

30

14. An implant as claimed in Claim 12 or 13 including a second pair of spaced abutment surfaces which extend at an angle to the first pair and which are also arranged to abut with correspondingly spaced opposed generally planar abutment surfaces of the bone.

35

- 13 -

15. An implant as claimed in Claim 14 in which the second pair of surfaces are comprised by an elongate rib of arcuate cross-section.
- 5 16. An implant as claimed in any of Claims 12 to 15 in which the first, or the first and second pairs of abutment surfaces are comprised on a first component.
- 10 17. An implant as claimed in any of Claims 12 to 16 including a third pair of spaced abutment surfaces spaced from the first and second pairs, the third pair of abutment surfaces facing away from each other, the third pair of abutment surfaces being arranged to abut with correspondingly spaced opposed generally planar abutment surfaces of a bone which face each other.
- 15 18. An implant as claimed in Claim 17 in which the planar abutment surfaces with which the third pair are arranged to cooperate are substantially parallel to each other.
- 20 19. An implant as claimed in Claim 17 or 18 including a fourth pair of spaced abutment surfaces which extend at an angle to the third pair and which are also arranged to abut with correspondingly spaced opposed generally planar abutment surfaces of a bone.
- 25 20. An implant as claimed in Claim 19 in which the fourth pair of surfaces are comprised by an elongate rib of partially arcuate cross-section.
- 30 21. An implant as claimed in any of Claims 17 to 20 in which the third or, alternatively the third and fourth pairs of abutment surfaces are comprised on a second component.

35

- 14 -

22. An implant as claimed in any of Claims 17 to 21 in which the third or the third and fourth pair of spaced abutment surfaces are arranged to cooperate with the surface of a vertebrae which faces the adjacent surface of an adjacent vertebrae with which the first or the first and second pair of abutment surfaces as claimed in any of Claims 12 to 16 are arranged to cooperate.

1/4




Fig.1a.




Fig.1b.

SUBSTITUTE SHEET

2/4




Fig. 2a.




Fig. 2b.




Fig. 2c.




Fig. 2d.




Fig. 2e.

SUBSTITUTE SHEET

3/4




Fig. 3a.




Fig. 3b.




Fig. 3c.




Fig. 3d.

SUBSTITUTE SHEET

4/4




Fig.4a.




Fig.4b.




Fig.4c.




Fig.4d.


SUBSTITUTE SHEET



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : A61F 2/44	A3	(11) International Publication Number: WO 93/10725 (43) International Publication Date: 10 June 1993 (10.06.93)
(21) International Application Number: PCT/GB92/02232 (22) International Filing Date: 1 December 1992 (01.12.92) (30) Priority data: 9125798.0 4 December 1991 (04.12.91) GB (71) Applicant (for all designated States except US): CUSTOM-FLEX LIMITED [GB/GB]; Unit 18A, Goldthorpe Industrial Estate, Goldthorpe, Rotherham, South Yorkshire S63 9BL (GB). (72) Inventor; and (75) Inventor/Applicant (for US only) : BULLIVANT, Michael [GB/GB]; 62 Cantley Lane, Bessacarr, Doncaster, South Yorkshire DN4 6NQ (GB). (74) Agents: SHERRARD-SMITH, Hugh et al.; Appleyard Lees, 15 Clare Road, GB-Halifax, West Yorkshire HX1 2HY (GB).		(81) Designated States: AT, AU, BB, BG, BR, CA, CH, CS, DE, DK, ES, FI, GB, HU, JP, KP, KR, LK, LU, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> (88) Date of publication of the international search report: 8 July 1993 (08.07.93)

(54) Title: IMPROVEMENTS IN OR RELATING TO SPINAL VERTEBRAE IMPLANTS



(57) Abstract

A plate (10) includes a raised platform (20) which rests in a channel in a vertebrae to prevent sideways movement of the plate. A rib (22) extends into a groove formed in the base of the channel to help prevent relative forwards and backwards movement of the plate (10) through the channel. A plate (12) is similarly secured to the facing surface of an adjacent vertebrae. A spacer (12) is inserted between the parts (10) and (14). The spacer (12) includes a downwardly facing convex surface (28) and a flat upwardly facing surface (30). The convex surface (28) slides in a concave recess (32) provided on top of the plate (14) and the flat surface (30) slides against a downwardly facing flat surface (34) of the upper plate (10).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CC	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 92/02232

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC Int.Cl.5 A 61 F 2/44		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
Int.Cl.5	A 61 F	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ⁸		
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹		
Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
A	WO,A,9113598 (J.B.S.) 19 September 1991, see claim 1; figures 1-3 <div style="text-align: center;">-----</div>	1
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>¹⁰ Special categories of cited documents :</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"A" document member of the same patent family</p> </div> </div>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
18-03-1993	10.06.93	
International Searching Authority	Signature of Authorized Officer	
EUROPEAN PATENT OFFICE		

INTERNATIONAL SEARCH REPORT

International application No.

PCT/GB92/02232

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 10 and 11
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

For further information see Form PCT/ISA/206 sent on 16.04.93.

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

1-9

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

GB 9202232
SA 67817

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A- 9113598	19-09-91	FR-A- 2659226	13-09-91
		AU-A- 7499191	10-10-91
		EP-A- 0471821	26-02-92
		JP-T- 4505574	01-10-92

THIS PAGE BLANK (USPTO)